



MEDICAL & PHARMACEUTICAL PACKAGING MACHINES

the **STARVIEW ADVANTAGE**

FROM MANUAL SHUTTLES, TO SEMI-AUTOMATIC ROTARIES TO FULLY
AUTOMATIC ROTARIES, CAROUSELS & INLINE PACKAGING MACHINES



FAB/PH8-1418
WITH AUTOMATED TYVEK LID FEED,
INK JET PRINTING,
VISION VERIFICATION – EJECT REJECT SYSTEM.

FAB8-1824-A

ERB/PH6-1418
WITH AUTOMATED TYVEK LID FEED,
& UNLOADER



CONSUMER GOODS



FOOD



MEDICAL DEVICE



PHARMACEUTICAL



NUTRACEUTICAL



AFTERMARKET PARTS

Markets we serve everyday

INNOVATIVE PACKAGING MACHINES
www.starviewpackaging.com

MEDICAL / PHARMACEUTICAL MODELS COMPARAISON

Click on miniature for more information about that series of Packaging Machines



SB/PH1-1012



SB/PH1



ERB/ PH4/PH6

Type of machine:	Table top shuttle	Manual shuttle	Semi-automatic rotary
Size type of production:	low	small	medium to high volume
Nominal sealing area:	10" x 12"	14" x 18" / 18" x 24" / 24" x 36"	14" x 18" / 18" x 24"
Number of open load stations:	1	1	3 or 5
Maximum blister depth:	3.0"	3.0"	3.0"
Heating system:	1 zone	multi zones	multi zones
Table Index:	N/A	N/A	Automatic
Tyvek feeder:	N/A	N/A	Optional attached or Self-standing
No. of automatic feeders:	N/A	N/A	Optional Tyvek feeder
Finished package unloader:	N/A	N/A	Optional
Electrical:	115 Volts / 1PH / 13 Amps	208-230 Volts / 1PH / 30 Amps or 208-230 Volts / 3PH / 25 Amps	208-230 Volts / 1PH / 25 or 55 Amps or 208-230 Volts / 3PH / 40 Amps



FAB/ PH6/PH8



BSC/PH



CBS/PH

Type of machine:	Fully automatic rotary	Fully automatic carousel	Fully automatic inline
Size type of production:	medium to high volume	high volume	high volume
Nominal sealing area:	14" x 18" / 18" x 24"	14" x 18" / 18" x 24"	14" x 28"
Number of open load stations:	2 or 4	3.25"	7
Maximum blister depth:	3.0"	Fully automatic	3.25"
Heating system:	multi zones	16	multi zones
Table Index:	Automatic	9	Automatic
Tyvek feeder:	Optional attached or Self-standing	Standard	Gravity drop standard / Transfer mechanism optional
No. of automatic feeders:	2	Standard	2
Finished package unloader:	Standard	Standard	Standard
Electrical:	208-230 Volts / 3PH / 25 or 45 Amps	208-230 Volts / 3PH / 50 Amps	208-230 Volts / 3PH / 50 Amps



SB/PH1-1012 SERIES MANUAL SHUTTLE FOR SAMPLING & PROTOTYPE MEDICAL & PHARMACEUTICAL MACHINE



SB1/PH1-1012

EXPERIENCE
the **STARVIEW**
ADVANTAGE
INNOVATIVE PACKAGING MACHINES

Starview Packaging Machinery, Inc.

Toll Free: 888-278-5555 www.starviewpackaging.com sales@starviewpackaging.com

SB/PH1-1012 SERIES MANUAL SHUTTLE FOR SAMPLING & PROTOTYPE MEDICAL & PHARMACEUTICA MACHINE

YOUR MARKET ... OUR SOLUTIONS

The **SB/PH1-1012 Series** single-station table top manual shuttle type heat sealers are designed for product development and package sampling. These machines are specifically designed for medical applications using foils, medical papers, Tyvek and other heat sealable lidstock.

For production machines please consider Starview's **SB/PH1-1418, 1824** or **1836** Series manual shuttle, **MS/PH1** Series auto-shuttle, **MR/PH2** Series manual rotary, **ERB/PH** Series semi automatic Rotary, **FAB/PH** automatic rotary or **CBS/PH** inline conveyor sealing machines.



the **STARVIEW** **ADVANTAGE**

- Color touch screen HMI for the ultimate in operator convenience and accessibility. Includes storage databases.
- A Starview exclusive remote access via an EWON remote system gives management access to real-time process information from the machine.
- On-screen temperature calibration standard with optional on-screen pressure calibration available to simplify validation using direct access validation ports.
- Economical table top machine for clean room or laminar flow hood operation to produce production equivalent prototype and sample packages.
- Generous use of stainless steel and polycarbonate in the structure for the most durable finish in the industry.
- Temperature and pressure validation using optional direct access ports for ease of connection.
- High pressure sealing press used in conjunction with matched aluminum tooling to give consistent sealing patterns with any heat sealable medical lidding materials.
- Industry leading design, construction, features and customer support.



CONSUMER GOODS



FOOD



MEDICAL DEVICE



PHARMACEUTICAL



NUTRACEUTICAL



AFTERMARKET PARTS

Markets we serve everyday

more on next page

SB/PH1-1012 SERIES SPECIFICATIONS

	SB/PH1-1012
Nominal sealing area:	10" x 12"
Number of open stations:	1
Heating system:	1 zone
Maximum tray depth:	3.0"
Average cycle speed:	1 – 6 cpm
Electrical:	115 volts / 1 PH / 13 Amps

Specifications and model availability are subject to change without notice.



Please request specific model quotations for complete pricing, specifications and options from your local distributor. Feel free to contact Starview to obtain the contact information for the authorized distributor in your area.



Starview Packaging Machinery, Inc.

Toll Free: 888-278-5555

www.starviewpackaging.com
sales@starviewpackaging.com



Copyright 2022 Starview Packaging Machinery, Inc.



SB/PH1 SERIES MANUAL SHUTTLE MEDICAL & PHARMACEUTICAL MACHINE



SB/PH1-1418
WITH OPTIONAL ALL ELECTRIC DRIVE,
AUTO SHUTTLE AND CASTERS



SB/PH1-1824
WITH OPTIONAL AUTO-SHUTTLE
AND CASTERS

EXPERIENCE
the **STARVIEW**
ADVANTAGE
INNOVATIVE PACKAGING MACHINES

Starview Packaging Machinery, Inc.

Toll Free: 888-278-5555 www.starviewpackaging.com sales@starviewpackaging.com

SB/PH1SERIES MANUAL SHUTTLE MEDICAL & PHARMACEUTICAL MACHINE

YOUR MARKET ... OUR SOLUTIONS

The **SB/PH1 Series** single-station floor model shuttle type heat sealers are designed for small to medium volume production requirements. These machines are specifically designed for medical applications using foils, medical paper, Tyvek and other heat sealable lidstock. These high- quality machines are ideal for start-up companies, back up equipment, cellular production lines or low volume in-house packaging. **SB/PH1 Series** machines are one (1) operator shuttle type sealers utilizing quick-change sealing fixtures.

For machines capable of higher production rates please consider Starview's **ERB/PH** Series semi automatic Rotary, **FAB/PH** automatic rotary or **CBS/PH** inline conveyor sealing machines.

the **STARVIEW** **ADVANTAGE**

- A wide range of standard and custom features available to match customer requirements.
- Generous use of stainless steel in the structure for the most durable finish in the industry.
- Color touch screen HMI for the ultimate in operator convenience and accessibility. Includes storage for 99 databases and on-screen data tracking.
- A Starview exclusive remote access via standard Ethernet hardwire or optional Wi-Fi router gives management access to real-time process information from the machine.
- On-screen temperature calibration standard with optional on-screen pressure calibration available to simplify validation using direct access validation ports.
- Ultra-high pressure sealing presses used in conjunction with matched aluminum tooling to give consistent sealing patterns with any heat sealable medical lidding materials.
- Industry leading design, construction, features and customer support.



Markets we serve everyday

more on next page

SB/PH1SERIES SPECIFICATIONS

	SB/PH1-1418	SB/PH1-1824
Nominal sealing area:	14" x 18"	18" x 24"
Number of open stations:	1	1
Heating system:	Multi zones	Multi zones
Maximum tray depth:	3.0"	3.0"
Average cycle speed:	1 – 6 cpm	1 – 6 cpm
Electrical:	208-230 volts / 1 PH / 30 Amps	208-230 Volts / 3 PH / 25 Amps

	SB/PH1-2430	SB/PH1-2436
Nominal sealing area:	24" x 30"	24" x 36"
Number of open stations:	1	1
Heating system:	Multi-zone cartridge	Multi-zone cartridge
Maximum tray depth:	3.0"	3.0"
Average cycle speed:	1 – 6 cpm	1 – 6 cpm
Electrical:	208-230 Volts / 3 PH / 25 Amps	208-230 Volts / 3 PH / 25 Amps

Specifications and model availability are subject to change without notice.



REQUEST
A
QUOTE

Please request specific model quotations for complete pricing, specifications and options from your local distributor. Feel free to contact Starview to obtain the contact information for the authorized distributor in your area.



Starview Packaging Machinery, Inc.

Toll Free: 888-278-5555

www.starviewpackaging.com

sales@starviewpackaging.com

Copyright 2022 Starview Packaging Machinery, Inc.





ERB/PH SERIES SEMI-AUTOMATIC ROTARY MEDICAL & PHARMACEUTICAL MACHINE



ERB/PH4



ERB/PH4
WITH OPTIONAL UNLOAD AND CASTERS



ERB/PH4
WITH OPTIONAL TYVEK LID FEED,
UNLOAD AND CONVEYOR



ERB/PH6
WITH OPTIONAL TYVEK LID FEED,
UNLOAD AND CASTERS

EXPERIENCE
the **STARVIEW**
ADVANTAGE
INNOVATIVE PACKAGING MACHINES

Starview Packaging Machinery, Inc.

Toll Free: 888-278-5555 www.starviewpackaging.com sales@starviewpackaging.com

ERB/PH SERIES

SEMI-AUTOMATIC ROTARY MEDICAL & PHARMACEUTICAL MACHINE

YOUR MARKET ... OUR SOLUTIONS

The **ERB/PH Series** rotary type heat sealers are designed for medium to higher volume production requirements. These machines are specifically designed for medical applications using foils, medical paper, Tyvek and other heat sealable lidstock. The ERB/PH Series units are available in four (4) and six (6) station designs. Models are available in standard sealing areas of 14 x 18 inches and 18 x 24 inches. Larger sealing areas are available on request. The standard machines feature one sealing station with the remaining stations used for operator loading and unloading.

For machines capable of higher production rates please consider Starview's **FAB/PH** automatic rotary or **CBS/PH** inline conveyor sealing machines.

the **STARVIEW** **ADVANTAGE**

- A wide range of standard and custom features available to match customer requirements.
- Generous use of stainless steel in the structure for the most durable finish in the industry.
- Color touch screen HMI for the ultimate in operator convenience and accessibility. Includes storage for 99 databases and on-screen data tracking.
- A Starview exclusive remote access via standard Ethernet hardwire or optional Wi-Fi router gives management access to real-time process information from the machine.
- On-screen temperature calibration standard with optional on-screen pressure calibration available to simplify validation using direct access validation ports.
- Ultra-high pressure sealing presses used in conjunction with matched aluminum tooling to give consistent sealing patterns with any heat sealable medical lidding materials.
- Precision indexing rotary table for precise sealing fixture to matching relieved face plate alignment.
- Industry leading design, construction, features and customer support.



Markets we serve everyday

more on next page

ERB/PH SERIES SPECIFICATIONS

	ERB/PH4-1418	ERB/PH4-1824
Nominal sealing area:	14" x 18"	18" x 24"
Number of open stations:	3	3
Heating system:	Multi zones	Multi zones
Table Index:	Automatic	Automatic
Tyvek feeder:	Optional attached or Self-standing	Optional attached or Self-standing
Maximum tray depth:	3.0"	3.0"
Average cycle speed:	1-15 cpm	1-12 cpm
Electrical:	208-230 Volts / 1 PH / 25 Amps	208-230 Volts / 1 PH / 25 Amps

	ERB/PH6-1418	ERB/PH6-1824
Nominal sealing area:	14" x 18"	18" x 24"
Number of open stations:	5	5
Heating system:	Multi zones	Multi zones
Table Index:	Automatic	Automatic
Tyvek feeder:	Optional attached or Self-standing	Optional attached or Self-standing
Maximum tray depth:	3.0"	3.0"
Average cycle speed:	1-15 cpm	1-12 cpm
Electrical:	208-230 Volts / 1 PH / 55 Amps or 208-230 Volts / 3 PH / 40 Amps	208-230 Volts / 1 PH / 55 Amps or 208-230 Volts / 3 PH / 40 Amps

Specifications and model availability are subject to change without notice.



Please request specific model quotations for complete pricing, specifications and options from your local distributor. Feel free to contact Starview to obtain the contact information for the authorized distributor in your area.



Starview Packaging Machinery, Inc.

Toll Free: 888-278-5555

www.starviewpackaging.com

sales@starviewpackaging.com

Copyright 2022 Starview Packaging Machinery, Inc.





FAB/PH SERIES FULLY AUTOMATIC ROTARY MEDICAL & PHARMACEUTICAL MACHINE



FAB//PH6-1824
WITH OPTIONAL PRODUCT FEEDER, AND FOLDOVER



FAB/PH8-1418

EXPERIENCE
the **STARVIEW**
ADVANTAGE
INNOVATIVE PACKAGING MACHINES

Starview Packaging Machinery, Inc.

Toll Free: 888-278-5555 www.starviewpackaging.com sales@starviewpackaging.com

FAB/PH SERIES

FULLY AUTOMATIC ROTARY MEDICAL & PHARMACEUTICAL MACHINE

YOUR MARKET ... OUR SOLUTIONS

The **FAB/PH Series** rotary type heat sealers are designed for medium to higher volume production requirements where automatic feeding and unloading is desired. These machines may be used for conventional carded blisters, full face blisters and half-clamshell styles as well as applications using medical paper, Tyvek, foils and other heat sealable lidstock. The **FAB/PH Series** units are available in six (6) and eight (8) station designs. Models are available in standard sealing areas of 14 x 18 inches and 18 x 24 inches. Larger sealing areas are available on request.

For machines capable of higher production rates please consider Starview's **CBS/PH** inline conveyor sealing machines.

the **STARVIEW** **ADVANTAGE**

- A wide range of standard and custom features available to match customer requirements.
- Generous use of stainless steel in the structure for the most durable finish in the industry.
- Color touch screen HMI for the ultimate in operator convenience and accessibility. Includes storage for 99 databases and on-screen data tracking.
- A Starview exclusive remote access via standard Ethernet hardwire or optional Wi-Fi router gives management access to real-time process information from the machine.
- On-screen temperature calibration standard with optional on-screen pressure calibration available to simplify validation using direct access validation ports.
- Ultra-high pressure sealing presses used in conjunction with matched aluminum tooling to give consistent sealing patterns with any heat sealable medical lidding materials. Hydro-pneumatic press available for cold seal materials.
- Precision indexing rotary table for precise sealing fixture to matching relieved face plate alignment.
- Industry leading design, construction, features and customer support.



Markets we serve everyday

more on next page

FAB/PH SERIES SPECIFICATIONS

	FAB/PH6-1418	FAB/PH6-1824
Nominal sealing area:	14" x 18"	18" x 24"
Number of open stations:	2	2
Table index:	Automatic	Automatic
Heating system:	Multi Zones	Multi Zones
No. of automatic feeders:	2	2
Finished package unloader:	Standard	Standard
Standard blister/tray depth:	3.0"	3.0"
Average cycle speed:	1 – 18 cpm	1 – 14 cpm
Electrical:	208-230 Volts / 3 PH / 25 Amps	208-230 Volts / 3 PH / 45 Amps

	FAB/PH8-1418	FAB/PH8-1824
Nominal sealing area:	14" x 18"	18" x 24"
Number of open stations:	4	4
Table index:	Automatic	Automatic
Heating system:	Multi Zones	Multi Zones
No. of automatic feeders:	2	2
Finished package unloader:	Standard	Standard
Standard blister/tray depth:	3.0"	3.0"
Average cycle speed:	1 – 18 cpm	1 – 16 cpm
Electrical:	208-230 Volts / 3 PH / 25 Amps	208-230 Volts / 3 PH / 45 Amps

Specifications and model availability are subject to change without notice.



REQUEST
A
QUOTE

Please request specific model quotations for complete pricing, specifications and options from your local distributor. Feel free to contact Starview to obtain the contact information for the authorized distributor in your area.



Starview Packaging Machinery, Inc.

Toll Free: 888-278-5555

www.starviewpackaging.com

sales@starviewpackaging.com

Copyright 2022 Starview Packaging Machinery, Inc.





CBS/PH SERIES FULLY AUTOMATIC INLINE MEDICAL & PHARMACEUTICAL MACHINE



CBS/PHA30-1428

EXPERIENCE
the **STARVIEW**
ADVANTAGE
INNOVATIVE PACKAGING MACHINES

Starview Packaging Machinery, Inc.

Toll Free: 888-278-5555 www.starviewpackaging.com sales@starviewpackaging.com

CBS/PH SERIES

FULLY AUTOMATIC INLINE MEDICAL & PHARMACEUTICAL MACHINE

YOUR MARKET ... OUR SOLUTIONS

The **CBS/PH Series** inline conveyor type heat sealers are designed for high volume production requirements. These machines may be used for pharmaceutical wallet pack as well as medical device applications using medical papers, Tyvek, foils and other heat sealable lidstock. Given the proper conditions these machines are capable of up to 20 cycles per minute in production. The Automated Inline Conveyor blister sealing machines are built with the capability to feed blister(s), tray(s), card(s), Tyvek and discharge finished packages when proper tooling is installed. With seven (7) open loading stations these machines are ideal for automated product loading or where multiple items are to be placed in a single package.

Machines with other sealing areas and different numbers of stations are also available. Consider Starview's **FAB/PH Series** for automatic rotary machines.

the **STARVIEW** **ADVANTAGE**

- A wide range of standard and custom features available to match customer requirements.
- Generous use of stainless steel in the structure for the most durable finish in the industry.
- Color touch screen HMI for the ultimate in operator convenience and accessibility. Includes storage for 99 databases and on-screen data tracking.
- A Starview exclusive remote access via standard Ethernet hardwire or optional Wi-Fi router gives management access to real-time process information from the machine.
- On-screen temperature calibration standard with optional on-screen pressure calibration available to simplify validation using direct access validation ports.
- Ultra-high pressure sealing presses used in conjunction with matched aluminum tooling to give consistent sealing patterns with any heat sealable medical lidding materials. Hydro-pneumatic press available for cold seal materials.
- Precision indexing rotary table for precise sealing fixture to matching relieved face plate alignment.
- Industry leading design, construction, features and customer support.



more on next page

CBS/PH SERIES SPECIFICATIONS

	CBS/PH30-1428	CBS/PHA30-1428
Sealing area:	14" x 28"	14" x 28"
Total no. of sealing fixtures:	30	30
Open loading stations:	7	7
Heating system:	Multi Zones	Multi Zones
Blister/tray feeder:	Optional	Standard
Tyvek / Card feeder:	Standard	Standard
Finished package unloader:	Gravity drop standard / Transfer mechanism optional	Gravity drop standard / Transfer mechanism optional
Maximum blister/tray depth:	3.5"	3.5"
Average cycle speed:	1-20 cpm	1-20 cpm
Electrical:	208-230 Volts / 3 PH / 50 Amps	208-230 Volts / 3 PH / 50 Amps

Specifications and model availability are subject to change without notice.



REQUEST
A
QUOTE

Please request specific model quotations for complete pricing, specifications and options from your local distributor. Feel free to contact Starview to obtain the contact information for the authorized distributor in your area.



Starview Packaging Machinery, Inc.

Toll Free: 888-278-5555

www.starviewpackaging.com

sales@starviewpackaging.com

Copyright 2022 Starview Packaging Machinery, Inc.

