



SKIN PACKAGING MACHINES

the **STARVIEW ADVANTAGE**

FROM MANUAL TO SEMI-AUTOMATIC TO
FULLY AUTOMATIC SKIN PACKAGING MACHINES



SP SERIES
24" X 36" AND SMALLER
WITH OPTIONAL CASTERS
AND FILM TEMPERATURE SENSOR



MSP-1218
WITH OPTIONAL
FLOOR STAND AND OUT FEED TABLE



CONSUMER GOODS



FOOD



MEDICAL DEVICE



PHARMACEUTICAL



NUTRACEUTICAL



AFTERMARKET PARTS

Markets we serve everyday

INNOVATIVE PACKAGING MACHINES
www.starviewpackaging.com

SKIN PACKAGING MACHINES

MODELS COMPARAISON

Click on miniature for more information about that series of Packaging Machines



MSP

Manual



SP & SP/IR

Semi-automatic



ASP

Fully automatic

Type of skin machine:	Manual	Semi-automatic	Fully automatic
Size type of productions:	Low volume	Medium to high volume	High volume
Max card size:	12" x 18" or 18" x 24"	18" x 24" to 36" x 48"	18" x 24" to 36" x 48"
Max product heigth:	8"	10"	6"
Heating system:	Quartz impulse	Quartz impulse (SP) or radiant panel (SP/IR)	Quartz impulse
Average cycle time:	30-60 seconds	15-45 seconds	15-60 seconds
Operator Light Curtain:	N/A	Optional (SP) or Standard (SP/IR)	Optional
Electrical:	208-230 Volts / 1 PH / 25 or 40 Amps	208-230 Volts / 3 PH / 32 to 100 Amps	208-230 Volts / 3 PH / 32 to 125 Amps



MSP SERIES MANUAL TABLE TOP SKIN PACKAGING MACHINE



MSP-1824
WITH OPTIONAL FLOOR STAND
AND OUT-FEED TABLE



EXPERIENCE
the **STARVIEW**
ADVANTAGE
INNOVATIVE PACKAGING MACHINES

Starview Packaging Machinery, Inc.

Toll Free: 888-278-5555

www.starviewpackaging.com

sales@starviewpackaging.com

MSP SERIES

MANUAL TABLE TOP SKIN PACKAGING MACHINE

YOUR MARKET ... OUR SOLUTIONS

The **MSP Series skin packaging machines** are designed for low volume applications. They incorporate a **stationary heating system with instant on/off heaters**, which come up to heat instantly during cycles and turn off for loading/unloading.

The **MSP skin packaging machines** have timer control for precision repeatability and an accurate turbine regulator. The **MSP Series** is available in the **standard size 12 by 18 inches and 18 by 24 inches**.

For larger machines with additional automation and higher levels of production please consider Starview's **SP & SP/IR Series** semi-automatic and **ASP & ASP/IR Series** fully automatic skin packaging machines.

the STARVIEW ADVANTAGE

- A **wide range** of standard and custom size machines available to **match customer requirements**.
- **HMI controls** for ease of operation.
- **Manual film clamping frame** operation does not require compressed air.
- Machines utilize industry standard film widths to facilitate film sourcing.
- **Industry leading design, construction, features and customer support.**



more on next page

MSP SERIES

SPECIFICATIONS

	MSP-1218	MSP-1824
Max card size:	12" x 18"	18" x 24"
Max product height:	8"	8"
Heating system:	Quartz impulse	Quartz impulse
Average cycle time:	30-60 seconds	30-60 seconds
Operator Light Curtain:	N/A	N/A
Electrical	208-230 Volts / 1 PH / 25 Amps	208-230 Volts / 1 PH / 40 Amps

Specifications and model availability are subject to change without notice.



REQUEST
A
QUOTE

Please request specific model quotations for complete pricing, specifications and options from your local distributor. Feel free to contact Starview to obtain the contact information for the authorized distributor in your area.



Starview Packaging Machinery, Inc.

Toll Free: 888-278-5555

www.starviewpackaging.com

sales@starviewpackaging.com

Copyright 2026 Starview Packaging Machinery, Inc.





SP & SP/IR SERIES SEMI-AUTOMATIC SKIN PACKAGING MACHINE

SP SERIES
24" X 48" AND LARGER
WITH OPTIONAL CASTERS
AND FILM TEMPERATURE SENSOR



SP SERIES
24" X 36" AND SMALLER
WITH OPTIONAL CASTERS
AND FILM TEMPERATURE SENSOR



SP/IR SERIES
WITH OPTIONAL
CASTERS, LIGHT CURTAINS AND
AUTOMATIC FILM CLAMPING SYSTEM

EXPERIENCE
the **STARVIEW**
ADVANTAGE
INNOVATIVE PACKAGING MACHINES

Starview Packaging Machinery, Inc.

Toll Free: 888-278-5555

www.starviewpackaging.com

sales@starviewpackaging.com

SP & SP/IR SERIES

SEMI-AUTOMATIC SKIN PACKAGING MACHINE

YOUR MARKET ... OUR SOLUTIONS

Starview's **SP Series** skin packaging machines are designed for low to medium volume applications. They incorporate a stationary heating system with instant on/off heaters, which come up to heat during cycles and turn off for loading/unloading.

The SP skin packaging machines have PLC timer control for precision repeatability and an accurate turbine regulator. A manual in-feed table, out-feed table and impulse type hot wire film cut-off are standard. These machines are a sturdy welded steel construction with removable panels for servicing.

The SP Series is available in the standard sizes beginning with 18 inches by 24 inches and also custom sizes. For machines with additional automation please consider our **ASP Series**.

the **STARVIEW** **ADVANTAGE**

- A wide range of standard and custom size machines available to match customer requirements.
- The only pendant mounted color touch screen HMI in the industry for the ultimate in operator convenience and accessibility.
- A Starview exclusive remote access via standard Ethernet hardwire or optional Wi-Fi router gives management access to process information from the machine.
- Fully adjustable vacuum motor speed and oven power using an on-screen touch bar graph to provide precise film temperature and vacuum control.
- Machine operating recipe storage including all timer and bar graph settings with memory for up to 99 different recipes for operator recall of proven set-ups for complex products.
- Industry leading design, construction, features and customer support.



Markets we serve everyday

more on next page

SP SERIES

SPECIFICATIONS

	SP-1824	SP-2430	SP-2436
Max card size:	18" x 24"	24" x 30"	24" x 36"
Max product height:	10"	10"	10"
Heating system:	Quartz impulse	Quartz impulse	Quartz impulse
Operator Light Curtain:	Optional	Optional	Optional
Average cycle time:	15-60 seconds	15-60 seconds	15-60 seconds
Electrical	208-240 Volts / 3 PH / 32 Amps	208-240 Volts / 3 PH / 55 Amps	208-240 Volts / 3 PH / 70 Amps

	SP-2448	SP-3036	SP-3048
Max card size:	24" x 48"	30" x 36"	30" x 48"
Max product height:	10"	10"	10"
Heating system:	Quartz impulse	Quartz impulse	Quartz impulse
Operator Light Curtain:	Standard	Standard	Standard
Average cycle time:	15-60 seconds	15-60 seconds	15-60 seconds
Electrical	208-240 Volts / 3 PH / 100 Amps	208-240 Volts / 3 PH / 80 Amps	208-240 Volts / 3 PH / 90 Amps

	SP-3648
Max card size:	36" x 48"
Max product height:	10"
Heating system:	Quartz impulse
Operator Light Curtain:	Standard
Average cycle time:	15-60 seconds
Electrical	208-240 Volts / 3 PH / 100 Amps

Specifications and model availability are subject to change without notice.

SP/IR SERIES

SPECIFICATIONS

	SP/IR-1824	SP/IR-2430
Max card size:	18" x 24"	24" x 30"
Max product height:	10"	10"
Heating system:	Radiant panel	Radiant panel
Operator Light Curtain:	Standard	Standard
Average cycle time:	15-45 seconds	15-45 seconds
Electrical	208-230 Volts / 3 PH / 50 Amps	208-230 Volts / 3 PH / 55 Amps

	SP/IR-2436	SP/IR-3036
Max card size:	24" x 36"	30" x 36"
Max product height:	10"	10"
Heating system:	Radiant panel	Radiant panel
Operator Light Curtain:	Standard	Standard
Average cycle time:	15-45 seconds	15-45 seconds
Electrical	208-230 Volts / 3 PH / 70 Amps	208-230 Volts / 3 PH / 80 Amps

Specifications and model availability are subject to change without notice.



Please request specific model quotations for complete pricing, specifications and options from your local distributor. Feel free to contact Starview to obtain the contact information for the authorized distributor in your area.



Starview Packaging Machinery, Inc.

Toll Free: 888-278-5555

www.starviewpackaging.com

sales@starviewpackaging.com

Copyright 2026 Starview Packaging Machinery, Inc.





ASP SERIES AUTOMATIC SKIN PACKAGING MACHINE



ASP-3036
WITH AUTOMATIC UNLOAD & CONVEYOR

EXPERIENCE
the **STARVIEW**
ADVANTAGE
INNOVATIVE PACKAGING MACHINES

Starview Packaging Machinery, Inc.

Toll Free: 888-278-5555 www.starviewpackaging.com sales@starviewpackaging.com

ASP SERIES

AUTOMATIC SKIN PACKAGING MACHINE

YOUR MARKET ... OUR SOLUTIONS

The **ASP Series** skin packaging machines are designed for low to medium volume applications. ASP machines incorporate a stationary heating system with instant on/off heaters. ASP skin packaging machines have PLC timer control for precision repeatability and an accurate turbine regulator. An automatic in-feed table with traveling template loader, out-feed table and impulse type hot wire cut-off are all standard. A multi-stage vacuum system for complex parts is included as a part of the HMI. A film temperature sensor that overrides the PLC heat timer for consistent film heating is standard.

Starview's **ASP Series** skin packaging machines can be equipped with an optional automatic overhead out-feed system. The PLC can be used to advance an optional conveyor to remove finished skin packages from the work area.

the **STARVIEW** **ADVANTAGE**

- A wide range of standard and custom size machines available to match customer requirements.
- The only pendant mounted color touch screen HMI in the industry for the ultimate in operator convenience and accessibility.
- A Starview exclusive remote access via standard Ethernet hardwire or optional Wi-Fi router gives management access to process information from the machine.
- Fully adjustable vacuum motor speed and oven power using an on-screen touch bar graph to provide precise film temperature and vacuum control.
- Machine operating recipe storage including all timer and bar graph settings with memory for up to 99 different recipes for operator recall of proven set-ups for complex products.
- Automatic template infeed and optional automatic outfeed designed to shorten loading and unloading times and reduce labor input.
- Industry leading design, construction, features and customer support.



Markets we serve everyday

more on next page

ASP SERIES

SPECIFICATIONS

	ASP-1824	ASP-2430	ASP-2436
Max card size:	18" x 24"	24" x 30"	24" x 36"
Max product height:	6"	6"	6"
Heating system:	Quartz impulse	Quartz impulse	Quartz impulse
Operator Light Curtain:	Optional	Optional	Optional
Average cycle time:	15-60 seconds	15-60 seconds	15-60 seconds
Electrical	208-240 Volts / 3 PH / 32 Amps	208-240 Volts / 3 PH / 55 Amps	208-240 Volts / 3 PH / 70 Amps

	ASP-3036	ASP-3048	ASP-3648
Max card size:	30" x 36"	30" x 48"	36" x 48"
Max product height:	6"	6"	6"
Heating system:	Quartz impulse	Quartz impulse	Quartz impulse
Operator Light Curtain:	Optional	Optional	Optional
Average cycle time:	15-60 seconds	15-60 seconds	15-60 seconds
Electrical	208-240 Volts / 3 PH / 84 Amps	208-240 Volts / 3 PH / 106 Amps	208-240 Volts / 3 PH / 125 Amps

Specifications and model availability are subject to change without notice.



Please request specific model quotations for complete pricing, specifications and options from your local distributor. Feel free to contact Starview to obtain the contact information for the authorized distributor in your area.



Starview Packaging Machinery, Inc.

Toll Free: 888-278-5555

www.starviewpackaging.com

sales@starviewpackaging.com

Copyright 2026 Starview Packaging Machinery, Inc.

