



RBF & RBFA SERIES SEMI & FULLY AUTOMATIC BOARD TO TRAY FOOD PACKAGING MACHINES



RBFA6 FULLY AUTOMATIC MODEL
SHOWN WITH ATTACHED LID FEEDER
AND FINISHED PACKAGE UNLOAD

EXPERIENCE
the **STARVIEW**
ADVANTAGE
INNOVATIVE PACKAGING MACHINES

Starview Packaging Machinery, Inc.

Toll Free: 888-278-5555

www.starviewpackaging.com

sales@starviewpackaging.com

RBF & RBFA SERIES

SEMI & FULLY AUTOMATIC BOARD TO TRAY FOOD PACKAGING MACHINES

YOUR MARKET ... OUR SOLUTIONS

Starview's **RBF & RBFA Series** rotary type heat sealers are designed for medium to higher volume production requirements. These machines are designed for producing all board heat sealable food containers. RBF & RBFA Series machines may also be used for conventional carded blisters, full face blisters and half-clamshell styles as well as applications using foils and other heat sealable lidstock. The RBF & RBFA Series units are available in six (6) station designs with a standard sealing area of 15 x 20 inches. Other sealing areas are available on request.

The standard RBF Series machines have one sealing station with the remaining five (5) stations used for tray loading and unloading. The RBFA Series machines feature one sealing station, one lid feeding station and one finished package unloading station with the remaining three (3) stations used for tray loading.

the **STARVIEW** **ADVANTAGE**

- A wide range of standard and custom features available to match customer requirements.
- AC Variable frequency precision cam index rotary table drive for smooth table operation and position repeatability.
- Standard Lid feeder and finished package unloader on RBFA models and optional finished package unloader on RBF models increase the machine versatility and lowers labor costs.
- Uses quick-change anodized aluminum tooling.
- Convenient touch screen controls for operator convenience, accessibility and process repeatability.
- A Starview exclusive remote access via standard Ethernet hardwire or optional Wi-Fi router gives management access to real-time process information from the machine.
- Starview's exclusive selectable sealing station program allows the use of one (1) through six (6) sealing fixtures with operator selected start position from HMI.
- Stainless steel wash down construction to allow cleaning in a food handling environment.
- Industry leading design, construction, features and customer support.



more on next page

RBF & RBFA SERIES

SPECIFICATIONS

	RBF6-1520	RBF6A-1520
Maximum tray dimensions:	15" x 20"	15" x 20"
Number of open stations:	5	3
Lid feeder:	N/A	Standard
Finished package unloader:	Optional-attached	Standard
Maximum tray depth:	3.0"	3.0"
Average cycle speed:	1 – 18 cpm	1 – 18 cpm
Electrical:	208-240 Volts / 1 PH / 32 Amps or 208-240 Volts / 3 PH / 19 Amps	208-240 Volts / 1 PH / 32 Amps or 208-240 Volts / 3 PH / 19 Amps

Specifications and model availability are subject to change without notice.



REQUEST
A
QUOTE

Please request specific model quotations for complete pricing, specifications and options from your local distributor. Feel free to contact Starview to obtain the contact information for the authorized distributor in your area.



Starview Packaging Machinery, Inc.

Toll Free: 888-278-5555

www.starviewpackaging.com

sales@starviewpackaging.com

Copyright 2026 Starview Packaging Machinery, Inc.

