



## FAB/PH SERIES FULLY AUTOMATIC ROTARY MEDICAL & PHARMACEUTICAL MACHINE

PHILLIPS  
FAB-PH8-1418



FAB/PH6-1824



FAB/PH8-1418



**EXPERIENCE**  
*the* **STARVIEW**  
**ADVANTAGE**  
INNOVATIVE PACKAGING MACHINES

Starview Packaging Machinery, Inc.

Toll Free: 888-278-5555    [www.starviewpackaging.com](http://www.starviewpackaging.com)    [sales@starviewpackaging.com](mailto:sales@starviewpackaging.com)

# FAB/PH SERIES

## FULLY AUTOMATIC ROTARY MEDICAL & PHARMACEUTICAL MACHINE

### YOUR MARKET ... OUR SOLUTIONS

The **FAB/PH Series** rotary type heat sealers are designed for medium to higher volume production requirements where automatic feeding and unloading is desired. These machines may be used for conventional carded blisters, full face blisters and half-clamshell styles as well as applications using medical paper, Tyvek, foils and other heat sealable lidstock. The **FAB/PH Series** units are available in six (6) and eight (8) station designs. Models are available in standard sealing areas of 14 x 18 inches and 18 x 24 inches. Larger sealing areas are available on request.

For machines capable of higher production rates please consider Starview's **CBS/PH** inline conveyor sealing machines.



FAB4-1012-CE

## the **STARVIEW** **ADVANTAGE**

- A wide range of standard and custom features available to match customer requirements.
- Generous use of stainless steel in the structure for the most durable finish in the industry.
- Color touch screen HMI for the ultimate in operator convenience and accessibility. Includes storage for 99 databases and on-screen data tracking.
- A Starview exclusive remote access via standard Ethernet hardwire or optional Wi-Fi router gives management access to real-time process information from the machine.
- On-screen temperature calibration standard with optional on-screen pressure calibration available to simplify validation using direct access validation ports.
- Ultra-high pressure sealing presses used in conjunction with matched aluminum tooling to give consistent sealing patterns with any heat sealable medical lidding materials. Hydro-pneumatic press available for cold seal materials.
- Precision indexing rotary table for precise sealing fixture to matching relieved face plate alignment.
- Industry leading design, construction, features and customer support.



CONSUMER GOODS

FOOD



MEDICAL DEVICE

PHARMACEUTICAL



NUTRACEUTICAL

AFTERMARKET PARTS

Markets we serve everyday

more on next page

# FAB/PH SERIES SPECIFICATIONS

|                              | FAB/PH6-1418                   | FAB/PH6-1824                   |
|------------------------------|--------------------------------|--------------------------------|
| Nominal sealing area:        | 14" x 18"                      | 18" x 24"                      |
| Number of open stations:     | 2                              | 2                              |
| Table index:                 | Automatic                      | Automatic                      |
| Heating system:              | Multi Zones                    | Multi Zones                    |
| No. of automatic feeders:    | 2                              | 2                              |
| Finished package unloader:   | Standard                       | Standard                       |
| Standard blister/tray depth: | 3.0"                           | 3.0"                           |
| Average cycle speed:         | 1 – 18 cpm                     | 1 – 14 cpm                     |
| Electrical:                  | 208-230 Volts / 3 PH / 25 Amps | 208-230 Volts / 3 PH / 45 Amps |

|                              | FAB/PH8-1418                   | FAB/PH8-1824                   |
|------------------------------|--------------------------------|--------------------------------|
| Nominal sealing area:        | 14" x 18"                      | 18" x 24"                      |
| Number of open stations:     | 4                              | 4                              |
| Table index:                 | Automatic                      | Automatic                      |
| Heating system:              | Multi Zones                    | Multi Zones                    |
| No. of automatic feeders:    | 2                              | 2                              |
| Finished package unloader:   | Standard                       | Standard                       |
| Standard blister/tray depth: | 3.0"                           | 3.0"                           |
| Average cycle speed:         | 1 – 18 cpm                     | 1 – 16 cpm                     |
| Electrical:                  | 208-230 Volts / 3 PH / 25 Amps | 208-230 Volts / 3 PH / 45 Amps |

*Specifications and model availability are subject to change without notice.*



Please request specific model quotations for complete pricing, specifications and options from your local distributor. Feel free to contact Starview to obtain the contact information for the authorized distributor in your area.



**Starview Packaging Machinery, Inc.**

Toll Free: 888-278-5555

[www.starviewpackaging.com](http://www.starviewpackaging.com)

[sales@starviewpackaging.com](mailto:sales@starviewpackaging.com)

Copyright 2026 Starview Packaging Machinery, Inc.

