



## FAB4, FAB6 & FAB8 APB SERIES FULLY AUTOMATIC ROTARY PAPER BLISTER SEALING MACHINES



FAB4-1012 APB  
SHOWN WITH OPTIONAL CASTER

FAB8-1418-APB  
WITH STAND ALONE FEEDER  
AND UNLOAD CONVEYOR

FAB8-1218.5 APB-AA  
**NEW SIZE**  
that utilizes your existing AA tooling

**EXPERIENCE**  
the **STARVIEW**  
**ADVANTAGE**  
INNOVATIVE PACKAGING MACHINES

Starview Packaging Machinery, Inc.

Toll Free: 888-278-5555

[www.starviewpackaging.com](http://www.starviewpackaging.com)

[sales@starviewpackaging.com](mailto:sales@starviewpackaging.com)

# FAB4, FAB6 & FAB8 APB SERIES

## FULLY AUTOMATIC ROTARY *PAPER BLISTER* SEALING MACHINES

### YOUR MARKET ... OUR SOLUTIONS

Starview's **FAB Series** fully automatic rotary type blister sealing machine is for all your blister packaging styles and materials. The **FAB APB AA** automated rotary blister sealing machine is built with the capability to feed and form paper blisters, or feed plastic blisters, feed blister cards, seal, and discharge finished packages with required quick-change tooling. These machines may be used for conventional carded blisters, trapped blisters, club store trapped packages, full face blisters and half-clamshell styles as well as some applications using foils, and other heat sealable lidstock materials

For other machines capable of higher finished package volumes or with additional open stations for automation please consider Starview's **BSC APB Series Carousel** or **CBS APB Series Inline machines**.

[Visit our APB website page](#) .

## the **STARVIEW** **ADVANTAGE**

- A wide range of standard and custom automation features available to match customer requirements.
- ANSI Class 4 machine safety for operator protection.
- Automatic blister feeder, card feeder & finished package unloader provide reduced labor costs.
- Color touch screen HMI for the ultimate in operator convenience and accessibility. Includes storage for 99 data bases and on-screen data tracking.
- A Starview exclusive remote access via standard Ethernet hardwire or optional Wi-Fi router gives management access to real-time process information from the machine.
- AC Variable frequency precision cam index rotary table drive for smooth table operation and position repeatability.
- Quick-change mounting for relieved face plates.
- Uses quick-change cost-effective multi-ply hardwood or durable aluminum tooling.
- Industry leading design, construction, features and customer support.



Markets we serve everyday

*more on next page*

# FAB4, FAB6 & FAB8 APB SERIES

## SPECIFICATIONS

### FAB4-1012 APB

|                             |                                |
|-----------------------------|--------------------------------|
| Sealing fixture size        | 10" x 12"                      |
| Nominal sealing area:       | 9" x 11"                       |
| Open loading stations:      | 1                              |
| Paper Blister feeder Gen 1: | yes                            |
| Paper Blister feeder Gen 2: | n/a                            |
| Card feeder(s):             | (1) Standard                   |
| Finished package unloader:  | Standard                       |
| Maximum blister depth:      | 1.25"                          |
| Average cycle speed:        | 1-15 cpm                       |
| Electrical:                 | 208-230 Volts / 1 PH / 25 Amps |

### FAB4-1216 APB

|                             |                            |
|-----------------------------|----------------------------|
| Sealing fixture size        | 11" x 16"                  |
| Nominal sealing area:       | 11" x 15"                  |
| Open loading stations:      | 1                          |
| Paper Blister feeder Gen 1: | yes                        |
| Paper Blister feeder Gen 2: | n/a                        |
| Card feeder(s):             | (1) Standard               |
| Finished package unloader:  | Standard                   |
| Maximum blister depth:      | 1.25"                      |
| Average cycle speed:        | 1-15 cpm                   |
| Electrical:                 | 220 Volts / 3 PH / 25 Amps |

### FAB6-1418 APB

|                             |                                |
|-----------------------------|--------------------------------|
| Sealing fixture size        | 14" x 18"                      |
| Nominal sealing area:       | 13" x 17"                      |
| Open loading stations:      | 2                              |
| Paper Blister feeder Gen 1: | yes                            |
| Paper Blister feeder Gen 2: | yes                            |
| Card feeder(s):             | (1) Standard                   |
| Finished package unloader:  | Standard                       |
| Maximum blister depth:      | 3.5"                           |
| Average cycle speed:        | 1-15 cpm                       |
| Electrical:                 | 208-230 Volts / 3 PH / 25 Amps |

### FAB8-1418 APB

|                             |                                |
|-----------------------------|--------------------------------|
| Sealing fixture size        | 14" x 18"                      |
| Nominal sealing area:       | 13" x 17"                      |
| Open loading stations:      | 4                              |
| Paper Blister feeder Gen 1: | yes                            |
| Paper Blister feeder Gen 2: | yes                            |
| Card feeder(s):             | (1) Standard                   |
| Finished package unloader:  | Standard                       |
| Maximum blister depth:      | 3.5"                           |
| Average cycle speed:        | 1-18 cpm                       |
| Electrical:                 | 208-230 Volts / 3 PH / 25 Amps |

### NEW!

### FAB8-1418-3 APB

|                             |                                |
|-----------------------------|--------------------------------|
| Sealing fixture size        | 14" x 18"                      |
| Nominal sealing area:       | 13" x 17"                      |
| Open loading stations:      | 3                              |
| Paper Blister feeder Gen 1: | yes                            |
| Paper Blister feeder Gen 2: | yes                            |
| Card feeder(s):             | (2) Standard                   |
| Finished package unloader:  | Standard                       |
| Maximum blister depth:      | 3.5"                           |
| Average cycle speed:        | 1-18 cpm                       |
| Electrical:                 | 208-230 Volts / 3 PH / 25 Amps |

### FAB8-1218.5 APB-AA

|                             |                                |
|-----------------------------|--------------------------------|
| Sealing fixture size        | 17.875" x 19.750"              |
| Nominal sealing area:       | 12 x 18.5                      |
| Open loading stations:      | 4                              |
| Paper Blister feeder Gen 1: | yes                            |
| Paper Blister feeder Gen 2: | yes                            |
| Card feeder(s):             | (1) Standard                   |
| Finished package unloader:  | Standard                       |
| Maximum blister depth:      | 3"                             |
| Average cycle speed:        | 1 – 18 cpm                     |
| Electrical:                 | 208-230 Volts / 3 PH / 25 Amps |

### FAB8-1824 APB

|                             |                                |
|-----------------------------|--------------------------------|
| Sealing fixture size        | 18" x 24"                      |
| Nominal sealing area:       | 17" x 23"                      |
| Open loading stations:      | 4                              |
| Paper Blister feeder Gen 1: | yes                            |
| Paper Blister feeder Gen 2: | yes                            |
| Card feeder(s):             | (1) Standard                   |
| Finished package unloader:  | Standard                       |
| Maximum blister depth:      | 3.5"                           |
| Average cycle speed:        | 1 – 18 cpm                     |
| Electrical:                 | 208-230 Volts / 3 PH / 45 Amps |

### FAB8-1824-3 APB

|                             |                                |
|-----------------------------|--------------------------------|
| Sealing fixture size        | 18" x 24"                      |
| Nominal sealing area:       | 17" x 23"                      |
| Open loading stations:      | 3                              |
| Paper Blister feeder Gen 1: | yes                            |
| Paper Blister feeder Gen 2: | yes                            |
| Card feeder(s):             | (2) Standard                   |
| Finished package unloader:  | Standard                       |
| Maximum blister depth:      | 3.5"                           |
| Average cycle speed:        | 1-18 cpm                       |
| Electrical:                 | 208-230 Volts / 3 PH / 45 Amps |

Specifications and model availability are subject to change without notice.



Please request specific model quotations for complete pricing, specifications and options from your local distributor. Feel free to contact Starview to obtain the contact information for the authorized distributor in your area.



**Starview Packaging Machinery, Inc.**

Toll Free: 888-278-5555

[www.starviewpackaging.com](http://www.starviewpackaging.com)

[sales@starviewpackaging.com](mailto:sales@starviewpackaging.com)

Copyright 2026 Starview Packaging Machinery, Inc.

